

Features

Finish: Exterior – Stainless Steel
Interior - Stainless Steel Bottom with Galvinised Sides

Insulation: High Density Polyurethane Foam Insulation
(CFC Free. Cyclopentane Blown)

Cooling System: Finned Evaporator – Fan Forced
Shelves: No. of Shelves – 2
Shelf Size – 555mm x 570mm
Shelf Construction - Welded Steel Frame With Epoxy-
polyester Powder Coating

Controller: Digital Controller Self Closing
Hinges And Wheels: Spring Assisted Hinges For Easy Closing
Lockable Castor Wheels



Optional Extras:

Glass Doors * (With Integrated LED Lights) |

Unit	Height	Width	Depth
FRG Dimensions (mm) (Full Door)	735	1135	575
FRG Dimensions (mm) (Half Door)	370	600	575
Cabinet Dimensions (mm)	915	1830	785
Packaging Dimensions (mm)	1000	1900	820

Literage	Total	FRZ	FRG
Gross Literage	610 L	N/A	610 L
Nett Literage	554 L	N/A	554 L

Loading:

20 Ft	40 Ft	40 Ft H/C	Tri Axle	Inter Link	Super Link
14	28	28	30	48	54

Model EB1850SS

Application	Under Bar
Model	EB 1850SS
Range	Commercial
Climate Class	Class 4
H.S. Code	8418.50.00
Footprint Area	1.43 m ²
Cord Length	2.4 m
Weight	127Kg
Weight Boxed	147Kg

* - Photo for illustrative purposes only. Actual unit may differ.

Q0830

Palfridge (LTD) – Design specifications

Confidentiality: This document contains information, which is confidential. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without prior permission in writing. If you have received this document in error, please notify Palfridge Ltd immediately by e-mail (info@palfridge.com), facsimile (+268 2 5184126) or telephone (+268 2 5184196) and thereafter return and/or destroy the document. Palfridge Ltd accepts no liability (to the fullest extent permitted by law) for information in this document, which does not relate to its official business. No contracts or official orders shall be concluded by means of this document. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE