

### Features

**Finish:** Chromadek Steel External & Internal

**Insulation:** High Density Polyurethane Foam Insulation  
(CFC Free. Cyclopentane Blown)

**Cooling System:** Ice Lined Evaporator With Wire on Tube  
Condenser

**Baskets:** No. of Baskets – 8  
Basket Size – 688mm x 225mm x 230mm  
Basket Capacity – 35.6 L  
Basket Construction - Welded Steel Frame With  
Epoxy-polyester Powder Coating

**Lid:** Free Sliding Low-E Toughened Glass Lids



### Optional Extras:

Voltage Protector | Stainless Steel Finish\*

Unit	Height	Width	Depth
FRZ Dimensions (mm)	630	2310	770
Cabinet Dimensions (mm)	785	2550	950
Packaging Dimensions (mm)	895	2610	1010

Literage	Total	FRZ	FRG
Gross Literage	988 L	988 L	N/A
Nett Literage	847 L	847 L	N/A

### Loading:

20 Ft	40 Ft	40 Ft H/C	Tri Axle	Inter Link	Super Link
8	16	24	24	36	36

### Model VS2500

Application	Freezer
Model	VS2500
Range	Commercial
Climate Class	Class 4
Star Rating	☆☆☆
H.S. Code	8418.30.00
FRZ Cap/24 <sup>Hrs</sup>	44.46Kg
Footprint Area	2.4 m <sup>2</sup>
Cord Length	2.4 m
Weight	189 Kg
Weight Boxed	230 Kg

R0130

\* - Photo for illustrative purposes only. Actual unit may differ.

Palfridge (LTD) – Design specifications

Confidentiality: This document contains information, which is confidential. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without prior permission in writing. If you have received this document in error, please notify Palfridge Ltd immediately by e-mail (info@palfridge.com), facsimile (+268 2 5184126) or telephone (+268 2 5184196) and thereafter return and/or destroy the document. Palfridge Ltd accepts no liability (to the fullest extent permitted by law) for information in this document, which does not relate to its official business. No contracts or official orders shall be concluded by means of this document. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE