

FEATURES

| | | |
|-------------------|--|---|
| Finish: | Chromadek Steel External & Internal | |
| Header Panel: | Size – 650mm x 185mm (0.12 m ²) Lighting – LED Tubes | |
| Decals: | Side – 585mm x 1970mm (1.15 m ²) | |
| Insulation: | High Density Polyurethane Foam Insulation (CFC Free, Cyclopentane Blown) | |
| Cooling System: | Forced Air Corrosion Resistant Evaporator | |
| Shelves: | No. of shelves – 4 (Adjustable) Shelf Size – 550mm x 435 mm (0.24 m ²) Shelf Construction - Welded Steel Frame With Epoxy-polyester Powder Coat | |
| Capacity: | Maximum (Double Stacked) 480 x 330ml cans | Optimum (Single Stacked) 240 x 330ml cans |
| Facing Per Shelf: | 7 x 330ml cans | |



OPTIONAL EXTRAS:

Branding & Decals* | One Additional Shelf | Voltage Protector | Shelf Talkers

| UNIT | Height | Width | Depth |
|-------------------------------|--------|-------|-------|
| FRG Dimensions (mm) | 1560 | 566 | 533 |
| Cabinet Dimensions (mm) | 1980 | 650 | 665 |
| Packaging Dimensions (mm) | 2005 | 660 | 675 |
| FRG Dimensions (inches) | 61.4 | 22.3 | 20.1 |
| Cabinet Dimensions (inches) | 78.0 | 25.6 | 26.2 |
| Packaging Dimensions (inches) | 78.9 | 28.3 | 28.1 |

Loading:

| 20 Ft | 40 Ft | 40Ft H/C |
|-------|-------|----------|
| 24 | 48 | 48 |

Model EH650

| | |
|----------------|---------------------|
| Application | Beverage Cooler |
| Model | EH 650 |
| Range | Commercial |
| Climate Class | Class 4 |
| H.S. Code | 8418.50.00 |
| Total Literage | 451L (15.9Cft) |
| FRG Literage | 451L (15.9Cft) |
| Footprint Area | 0.43 m ² |
| Cord Length | 2.4 m |
| Weight | 85.0Kg |
| Weight Boxed | 89.0Kg |

COMPRESSOR:

| Refrigerant | Gas Charge | Start Current | Run Current | Energy Cons. |
|-------------|------------|---------------|-------------|-----------------------------|
| R600 | 70 Grams | 7.02 A | 2.24 A | 3.98 Kw / 24 ^{Hrs} |

01014

* - Photo for illustrative purposes only. Actual unit may differ.