

FEATURES

Finish:	Chromadek Steel External Sides & Internal
Header Panel:	Size – 650mm 185mm Lighting – LED
Insulation:	High Density Polyurethane Foam Insulation (CFC Free. Cyclopentane Blown)
Cooling System:	Frost Free Forced Air Corrosion Resistant Evaporator
Shelves:	No. of shelves – 4 Shelf Size – 500mm x 440 mm Shelf Construction – Wire powder coated appliance white
Controller:	Electronic Controller



OPTIONAL EXTRAS:

Branding & Decals* | Voltage Protector | Shelf Talkers | Stainless Steel External Sides* | Galvanised Steel External Sides*

UNIT	Height	Width	Depth
FRZ Dimensions (mm)	1555	530	510
Cabinet Dimensions (mm)	1980	650	660
Packaging Dimensions (mm)	2020	660	630

Literage	Total	FRZ	FRG
Gross Literage	420 L	420 L	N/A
Nett Literage	409 L	409 L	N/A

Loading:					
20 Ft	40 Ft	40 Ft	Tri	Inter	Super
		H/C	Axle	Link	Link
27	57	57	60	100	84

Model EU660

Type	Upright freezer
Model	EU 660
Range	Commercial
Climate Class	Class 4
Footprint Area	0.43 m ²
Cord Length	2.4 m
Weight	
Weight Boxed	

Q0705

* - Photo for illustrative purposes only. Actual unit may differ.

Palfridge (LTD) – Design specifications

Confidentiality: This document contains information, which is confidential. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without prior permission in writing. If you have received this document in error, please notify Palfridge Ltd immediately by e-mail (info@palfridge.com), facsimile (+268 2 5184126) or telephone (+268 2 5184196) and thereafter return and/or destroy the document. Palfridge Ltd accepts no liability (to the fullest extent permitted by law) for information in this document, which does not relate to its official business. No contracts or official orders shall be concluded by means of this document. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE