

MODEL ES1140SL Beverage Cooler 748 Liter Capacity

Features

Finish:	Chromadek Steel External & Internal	
Header Panel:	Size – 1140mm x 275mm (Visible 1105mm x 205mm) Lighting – LED	
Decals:	Side –540mm x 1970mm (1.26 m ²)	
Insulation:	High Density Polyurethane Foam Insulation (CFC Free. Cyclopentane Blown)	
Cooling System:	Forced Air Corrosion Resistant Evaporator	
Shelves:	No. of shelves – 8 (4 Per Door - Adjustable) Shelf Size – 495mm x 395 mm (0.2 m ²) Shelf Construction - Welded Steel Frame With Epoxy- polyester Powder Coat	
Capacity:	Maximum (Double Stacked) 840 x 330ml cans	Optimum (Single Stacked) 420 x 330ml cans
Facing Per Shelf:	7 x 330ml cans	
Operating Ambient:	32°C and 60% Relative Humidity**	



OPTIONAL EXTRAS:

Branding & Decals* | Two Additional Shelves | Voltage Protector | Shelf Talkers | Stainless Steel External Sides
| Galvanized Steel External Sides | Low E Doors**

Unit	Height	Width	Depth
FRG Dimensions (mm)	1600	1050	445
Cabinet Dimensions (mm)	2000	1140	545
Packaging Dimensions (mm)	2020	1150	555

Literage	Total	FRZ	FRG
Gross Literage	748 L	N/A	748 L
Nett Literage	663 L	N/A	663 L

Loading:

20 Ft	40 Ft	40 Ft H/C	Tri Axle	Inter Link	Super Link
20	42	42	46	60	64

Model ES1140SL

Type	Beverage Cooler
Model	ES1140SL
Range	Commercial
Climate Class	Class 4
H.S. Code	8418.50.00
Footprint Area	0.70 m ²
Cord Length	2.4 m
Weight	125.0Kg
Weight Boxed	130.0Kg

R0306

* - Photo for illustrative purposes only. Actual unit may differ.

** - If operating ambient conditions are higher, unit will require "Low E" doors to prevent condensation on glass.

Palfridge (LTD) – Design specifications

Confidentiality: This document contains information, which is confidential. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without prior permission in writing. If you have received this document in error, please notify Palfridge Ltd immediately by e-mail (info@palfridge.com), facsimile (+268 2 5184126) or telephone (+268 2 5184196) and thereafter return and/or destroy the document. Palfridge Ltd accepts no liability (to the fullest extent permitted by law) for information in this document, which does not relate to its official business. No contracts or official orders shall be concluded by means of this document. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE