

### FEATURES

Finish:	Chromadek Steel External Sides & Internal Cabinet	
Header Panel:	Size – 1120mm x 195mm (Visible 1090mm x 165mm) Lighting – LED Tube	
Decals:	Side – 560mm x 1320mm (0.58 m <sup>2</sup> )	
Insulation:	High Density Polyurethane Foam Insulation (CFC Free. Cyclopentane Blown)	
Cooling System:	Forced Air Corrosion Resistant Evaporator	
Shelves:	No. of shelves – 4 (Adjustable) Shelf Size – 450mm x 490 mm (0.22 m <sup>2</sup> ) Shelf Construction - Welded Steel Frame With Epoxy-polyester Powder Coat	
Capacity:	Maximum (Double Stacked) 336 x 330ml cans	Optimum (Single Stacked) 168 x 330ml cans
Facing Per Shelf:	7 x 330ml cans	



### OPTIONAL EXTRAS:

Branding & Decals | Voltage Protector | Shelf Talkers |

UNIT	Height	Width	Depth
FRG Dimensions (mm)	937	1050	600
Cabinet Dimensions (mm)	1330	1130	695
Packaging Dimensions (mm)	1355	1180	745

Literage	Total	FRZ	FRG
Gross Literage	476 L	N/A	476 L
Nett Literage	460 L	N/A	460 L

Loading:0					
20 Ft	40 Ft	40 Ft	Tri	Inter	Super
		H/C	Axle	Link	Link
15	30	30	34	44	48

### Model EF 476

Type	Beverage Cooler
Model	EF476
Range	Commercial
Climate Class	Class "N "
H.S. Code	8418.50.00
Footprint Area	0.84 m <sup>2</sup>
Cord Length	2.4 m
Weight	
Weight Boxed	

### COMPRESSOR:

Refrigerant	Gas Charge	Start Current	Run Current	Energy Cons.
R290	130 Grams	8.8 A	3.8 A	3.16 Kw / 24 <sup>Hrs</sup>

P0428

\* - Photo for illustrative purposes only. Actual unit may differ.