

### FEATURES

**Finish:** Pre-painted Galvanised Steel External & Internal

**Insulation:** High Density Polyurethane Foam Insulation  
(CFC Free, Cyclopentane Blown)

**Cooling System:** Ice Lined Evaporator With Wire on Tube  
Condenser

**Baskets:** No. of Baskets – 6  
Basket Size – 785mm x 260mm x 280mm  
Basket Capacity – 34.78 L  
Basket Construction - Welded Steel Frame With  
Epoxy-polyester Powder Coating

**Lid:** Free Sliding Toughened Glass Lids



### Optional Extras:

Voltage Protector | Stainless Steel Finish

Unit	Height	Width	Depth
FRZ Dimensions (mm)	630	1810	770
Cabinet Dimensions (mm)	785	2050	950
Packaging Dimensions (mm)	895	2150	1010

Literage	Total	FRZ	FRG
Gross Literage	820 L	820 L	N/A
Nett Literage	707 L	707 L	N/A

Loading:					
20 Ft	40 Ft	40 Ft	Tri	Inter	Super
		H/C	Axle	Link	Link
10	22	22	24	32	34

### Model VS2000

Application	Freezer
Model	VS2000
Range	Commercial
Climate Class	Class 4
Star Rating	☆☆☆
H.S. Code	8418.30.00
FRZ Cap/24 <sup>Hrs</sup>	36.9Kg
Footprint Area	1.9 m <sup>2</sup>
Cord Length	2.4 m
Weight	
Weight Boxed	

\* - Photo for illustrative purposes only. Actual unit may differ.

Q0705

Palfridge (LTD) – Design specifications

Confidentiality: This document contains information, which is confidential. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without prior permission in writing. If you have received this document in error, please notify Palfridge Ltd immediately by e-mail (info@palfridge.com), facsimile (+268 2 5184126) or telephone (+268 2 5184196) and thereafter return and/or destroy the document. Palfridge Ltd accepts no liability (to the fullest extent permitted by law) for information in this document, which does not relate to its official business. No contracts or official orders shall be concluded by means of this document. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE