

Features

| | | |
|---------------------------|--|---|
| Finish: | Chromadek Steel External & Internal | |
| Header Panel: | Size – 1140mm x 275mm (Visible 1105mm x 205mm) Lighting – LED | |
| Decals: | Side –640mm x 1970mm (1.26 m ²) | |
| Insulation: | High Density Polyurethane Foam Insulation (CFC Free. Cyclopentane Blown) | |
| Cooling System: | Forced Air Corrosion Resistant Evaporator | |
| Shelves: | No. of shelves – 8 (4 Per Door - Adjustable) Shelf Size – 495mm x 480 mm (0.24 m ²) Shelf Construction - Welded Steel Frame With Epoxy- polyester Powder Coat | |
| Capacity: | Maximum (Double Stacked) 980 x 330ml cans | Optimum (Single Stacked) 490 x 330ml cans |
| Facing Per Shelf: | 7 x 330ml cans | |
| Operating Ambient: | 32°C and 60% Relative Humidity** | |



OPTIONAL EXTRAS:

Branding & Decals* | Two Additional Shelves | Voltage Protector | Shelf Talkers | Stainless Steel External Sides
| Galvanized Steel External Sides | Low E Doors**

| Unit | Height | Width | Depth |
|---------------------------|--------|-------|-------|
| FRG Dimensions (mm) | 1600 | 1050 | 530 |
| Cabinet Dimensions (mm) | 1980 | 1140 | 700 |
| Packaging Dimensions (mm) | 2005 | 1150 | 640 |

| Literage | Total | FRZ | FRG |
|----------------|-------|-----|-------|
| Gross Literage | 885 L | N/A | 885 L |
| Nett Literage | 772 L | N/A | 772 L |

Loading:

| 20 Ft | 40 Ft | 40 Ft H/C | Tri Axle | Inter Link | Super Link |
|-------|-------|--------------|-------------|---------------|---------------|
| 18 | 36 | 36 | 40 | 56 | 56 |

Model ES1140

| | |
|----------------|---------------------|
| Type | Beverage Cooler |
| Model | ES1140 |
| Range | Commercial |
| Climate Class | Class 4 |
| H.S. Code | 8418.50.00 |
| Footprint Area | 0.80 m ² |
| Cord Length | 2.4 m |
| Weight | 132.0Kg |
| Weight Boxed | 137.0Kg |

* - Photo for illustrative purposes only. Actual unit may differ.

** - If operating ambient conditions are higher, unit will require "Low E" doors to prevent condensation on glass.

R0306

Palfridge (LTD) – Design specifications

Confidentiality: This document contains information, which is confidential. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without prior permission in writing. If you have received this document in error, please notify Palfridge Ltd immediately by e-mail (info@palfridge.com), facsimile (+268 2 5184126) or telephone (+268 2 5184196) and thereafter return and/or destroy the document. Palfridge Ltd accepts no liability (to the fullest extent permitted by law) for information in this document, which does not relate to its official business. No contracts or official orders shall be concluded by means of this document. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE