

FEATURES

Finish:	Chromadek Steel External & Internal
Insulation:	High Density Polyurethane Foam Insulation (CFC Free. Cyclopentane Blown)
Cooling System:	Ice Lined Evaporator With Wire on Tube Condenser
Baskets:	No. of Baskets – 6 Basket Size – 688mm x 225mm x 230mm Basket Capacity – 35.6 L Basket Construction - Welded Steel Frame With Epoxy-polyester Powder Coating
Lid:	Free Sliding Low-E Toughened Glass Lids



Optional Extras:

Voltage Protector | Stainless Steel Finish

Unit	Height	Width	Depth
FRZ Dimensions (mm)	630	1870	770
Cabinet Dimensions (mm)	785	2050	950
Packaging Dimensions (mm)	895	2150	1010

Literage	Total	FRZ	FRG
Gross Literage	862 L	862 L	N/A
Nett Literage	862 L	862 L	N/A

Loading:

20 Ft	40 Ft	40 Ft H/C	Tri Axle	Inter Link	Super Link
10	22	33	36	48	51

Model VS2000

Application	Freezer
Model	VS2000
Range	Commercial
Climate Class	Class 4
H.S. Code	8418.50 8
FRZ Cap/24 ^{Hrs}	38.79Kg
Footprint Area	1.9 m ²
Cord Length	2.4 m
Weight	153 Kg
Weight Boxed	189 Kg

* - Photo for illustrative purposes only. Actual unit may differ.

R0530

Palfridge (LTD) – Design specifications

Confidentiality: This document contains information, which is confidential. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without prior permission in writing. If you have received this document in error, please notify Palfridge Ltd immediately by e-mail (info@palfridge.com), facsimile (+268 2 5184126) or telephone (+268 2 5184196) and thereafter return and/or destroy the document. Palfridge Ltd accepts no liability (to the fullest extent permitted by law) for information in this document, which does not relate to its official business. No contracts or official orders shall be concluded by means of this document. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE