

Features

Finish: Chromadek Steel External Sides & Internal Cabinet

Insulation: High Density Polyurethane Foam Insulation (CFC Free, Cyclopentane Blown)

Cooling System: Skin Evaporator

Baskets: No. of Baskets – 4
Basket Size – 325mm x 525mm x 230mm
Basket Capacity – 39.2 L
Basket Construction - Welded Steel Frame With Epoxy-polyester Powder Coating

Wheels: Castor Wheels



Optional Extras:

Voltage Protector | Stainless Steel Finish

Unit	Height	Width	Depth
FRZ Dimensions (mm)	695	1350	525
Cabinet Dimensions (mm)	860	1450	650
Packaging Dimensions (mm)	900	1490	695

Literage	Total	FRZ	FRG
Gross Literage	520 L	520 L	N/A
Nett Literage	498 L	498 L	N/A

Loading:					
20 Ft	40 Ft	40 Ft	Tri	Inter	Super
		H/C	Axle	Link	Link
24	48	48	48	66	72

Model VL525

Type	Freezer
Model	VL525
Range	Commercial
Climate Class	Class 4
Star Rating	☆☆☆
H.S. Code	8418.30.00
FRZ Cap/24 ^{Hrs}	23.4Kg
Footprint Area	0.94 m ²
Cord Length	2.4 m
Weight	90 Kg
Weight Boxed	97 Kg

Compressor:

Refrigerant	Gas Charge	Start Current	Run Current	Energy Cons.
R290	65 Grams	6.75 A	2.45 A	3.99 Kwh / 24 ^{Hrs}

Q0705

* - Photo for illustrative purposes only. Actual unit may differ.

Palfridge (LTD) – Design specifications

Confidentiality: This document contains information, which is confidential. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without prior permission in writing. If you have received this document in error, please notify Palfridge Ltd immediately by e-mail (info@palfridge.com), facsimile (+268 2 5184126) or telephone (+268 2 5184196) and thereafter return and/or destroy the document. Palfridge Ltd accepts no liability (to the fullest extent permitted by law) for information in this document, which does not relate to its official business. No contracts or official orders shall be concluded by means of this document. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE