

FEATURES

Finish: Stainless Steel External & Pre-painted Galvanised Steel Internal

Insulation: High Density Polyurethane Foam Insulation (CFC Free, Cyclopentane Blown)

Cooling System: Finned Evaporator – Fan Forced

Shelves: No. of Shelves – 2
Shelf Size – 700mm x 400mm
Shelf Construction - Welded Steel Frame With Epoxy-polyester Powder Coating

Hinges: Spring Assisted Hinges For Easy Closing



Optional Extras:

Unit	Height	Width	Depth
FRZ Dimensions (mm)	745	820	420
Cabinet Dimensions (mm)	850	900	600
Packaging Dimensions (mm)	950	960	660
FRG Dimensions (inches)	29.3	32.3	16.5
Cabinet Dimensions (inches)	33.5	35.4	23.6
Packaging Dimensions (inches)	37.4	39.4	27.6

Loading:

20 Ft	40 Ft	40Ft H/C
36	72	72

Model ER900

Application	Back Of Bar
Model	ER 900
Range	Commercial
Climate Class	Class 4
H.S. Code	8418.50.00
Total Litrage	263L (9.3CFt)
FRG Litrage	263L (9.3CFt)
Footprint Area	0.54 m ²
Cord Length	2.4 m
Weight	
Weight Boxed	

COMPRESSOR:

Refrigerant	Gas Charge	Start Current	Run Current	Energy Cons.
R600a	45 Grams	2.85 A	1.2 A	3.11 Kw/ 24 ^{Hrs}

* - Photo for illustrative purposes only. Actual unit may differ.

O0224

Palfridge (LTD) – Design specifications

Confidentiality: This document contains information, which is confidential. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without prior permission in writing. If you have received this document in error, please notify Palfridge Ltd immediately by e-mail (info@palfridge.com), facsimile (+268 2 5184126) or telephone (+268 2 5184196) and thereafter return and/or destroy the document. Palfridge Ltd accepts no liability (to the fullest extent permitted by law) for information in this document, which does not relate to its official business. No contracts or official orders shall be concluded by means of this document. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE