

### FEATURES

**Finish:** Black Chromadek Steel External & Internal

**Insulation:** High Density Polyurethane Foam Insulation  
(CFC Free. Cyclopentane Blown)

**Cooling System:** Finned Evaporator – Fan Forced

**Shelves:** No. of Shelves – 2  
Shelf Size – 1014mm x 330mm  
Shelf Construction - Welded Steel Frame With  
Epoxy-polyester Powder Coating



### Optional Extras:

Unit	Height	Width	Depth
FRG Dimensions (mm)	720	1025	480
Cabinet Dimensions (mm)	895	1130	595
Packaging Dimensions (mm)	940	1170	660

Literage	Total	FRZ	FRG
Gross Literage	328 L	N/A	328 L
Nett Literage	242 L	N/A	242 L

### Loading:

20 Ft	40 Ft	40 Ft	Tri	Inter	Super
		H/C	Axle	Link	Link
34	68	68	76	100	104

### Model ER900BG

Application	Back Of Bar
Model	ER 900 BG
Range	Commercial
Climate Class	Class 4
H.S. Code	8418.50.00
Footprint Area	0.54 m <sup>2</sup>
Cord Length	2.4 m
Weight	
Weight Boxed	

\* - Photo for illustrative purposes only. Actual unit may differ.

Q0824

Palfridge (LTD) – Design specifications

Confidentiality: This document contains information, which is confidential. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without prior permission in writing. If you have received this document in error, please notify Palfridge Ltd immediately by e-mail (info@palfridge.com), facsimile (+268 2 5184126) or telephone (+268 2 5184196) and thereafter return and/or destroy the document. Palfridge Ltd accepts no liability (to the fullest extent permitted by law) for information in this document, which does not relate to its official business. No contracts or official orders shall be concluded by means of this document. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE