

FEATURES

Finish:	Chromadek Steel External Sides & Internal Durable Marble Patterned Lid
Insulation:	High Density Polyurethane Foam Insulation (CFC Free. Cyclopentane Blown)
Cooling System:	Ice Lined Evaporator With Static Rear Condenser
Baskets:	No. of Baskets – 3 Basket Size – 230mm x 260mm x 575mm Basket Capacity – 29.9 L (1.1 CFT) Basket Construction - Welded Steel Frame With Epoxy-polyester Powder Coating
Locks & Hinges:	SABS Approved Key Lock Spring Assisted Steel Hinges For Easy Opening



Optional Extras:

Voltage Protector | Stainless Steel Finish

Unit	Height	Width	Depth
FRZ Dimensions (mm)	738	1532	550
Cabinet Dimensions (mm)	870	1635	735
Packaging Dimensions (mm)	890	1660	740

Literage	Total	FRZ	FRG
Gross Literage	567 L	567 L	N/A
Nett Literage	567 L	567 L	N/A

Loading:

20 Ft	40 Ft	40 Ft H/C	Tri Axle	Inter Link	Super Link
18	42	63	63	90	90

Model CF590

Application	Freezer
Model	CF 590
Range	Commercial
Climate Class	Class N
Star Rating	☆☆☆
H.S. Code	8418.30.00
U.N. Code	44811-2
FRZ Cap/24 ^{Hrs}	25.52Kg
Footprint Area	1.06 m ²
Cord Length	2.4 m
Weight	84Kg
Weight Boxed	89.5Kg

* - Photo for illustrative purposes only. Actual unit may differ.

Q1025

Palfridge (LTD) – Design specifications

Confidentiality: This document contains information, which is confidential. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without prior permission in writing. If you have received this document in error, please notify Palfridge Ltd immediately by e-mail (info@palfridge.com), facsimile (+268 2 5184126) or telephone (+268 2 5184196) and thereafter return and/or destroy the document. Palfridge Ltd accepts no liability (to the fullest extent permitted by law) for information in this document, which does not relate to its official business. No contracts or official orders shall be concluded by means of this document. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE