

### FEATURES

**Finish:** Chromadek Steel External & Internal

**Insulation:** High Density Polyurethane Foam Insulation  
(CFC Free. Cyclopentane Blown)

**Cooling System:** Ice Lined Evaporator With Fan Cooled Condenser

**Capacity:** No. of Compartments – 4  
Compartment Size – 620mm x 372mm x 485mm  
Construction - Welded Steel Frame With Epoxy-  
polyester Powder Coating

**Lid:** Free Sliding Low-E Toughened Glass Lids

**Lights:** LED Lighting



**Optional Extras:**  
Voltage Protector |

Unit	Height	Width	Depth
FRZ Dimensions (mm)	690	1710	700
Cabinet Dimensions (mm)	935	1875	870
Packaging Dimensions (mm)	980	1930	1000

Literage	Total	FRZ	FRG
Gross Literage	758 L	758 L	N/A
Nett Literage	753 L	753 L	N/A

### Loading:

20 Ft	40 Ft	40 Ft H/C	Tri Axle	Inter Link	Super Link
10	20	20	24	32	36

### Model VT 1850

Application	Island Freezer
Model	VT1850
Range	Commercial
Climate Class	Class 4
Star Rating	☆☆☆
H.S. Code	8418.30.00
FRZ Cap/24 <sup>Hrs</sup>	34.1Kg
Footprint Area	1.63 m <sup>2</sup>
Cord Length	2.4 m
Weight	112Kg
Weight Boxed	142Kg

R0131

\* - Photo for illustrative purposes only. Actual unit may differ.

Palfridge (LTD) – Design specifications

Confidentiality: This document contains information, which is confidential. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without prior permission in writing. If you have received this document in error, please notify Palfridge Ltd immediately by e-mail (info@palfridge.com), facsimile (+268 2 5184126) or telephone (+268 2 5184196) and thereafter return and/or destroy the document. Palfridge Ltd accepts no liability (to the fullest extent permitted by law) for information in this document, which does not relate to its official business. No contracts or official orders shall be concluded by means of this document. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE