

FEATURES

Finish:	Chromadek Steel External Sides & Internal Cabinet
Decals:	Front –800mm x 775mm (0.62 m ²) Side – 550mm x 775mm (0.42 m ²)
Insulation:	High Density Polyurethane Foam Insulation (CFC Free. Cyclopentane Blown)
Cooling System:	Ice Lined Evaporator With Static Rear Condenser
Baskets:	No. of Baskets – 3 Basket Size – 285mm x 225mm x 480mm Basket Capacity – 17 L Basket Construction - Welded Steel Frame With Epoxy-polyester Powder Coating
Wheels:	castor wheels



Optional Extras:

Voltage Protector | Stainless Steel Finish*

Unit	Height	Width	Depth
FRZ Dimensions (mm)	705	695	445
Cabinet Dimensions (mm)	860	810	575
Packaging Dimensions (mm)	970	825	655

Literage	Total	FRZ	FRG
Gross Literage	197 L	197 L	N/A
Nett Literage	197 L	197 L	N/A

Loading:

20 Ft	40 Ft	40 Ft	Tri	Inter	Super
		H/C	Axle	Link	Link
42	84	84	90	150	126

Model VL222

Type	Freezer
Model	VL222
Range	Commercial
Climate Class	Class 4
Star Rating	☆☆☆
H.S. Code	8418.30.00
FRZ Cap/24 ^{Hrs}	8.9Kg
Footprint Area	0.47 m ²
Cord Length	1.5 m
Weight	
Weight Boxed	

Q0705

* - Photo for illustrative purposes only. Actual unit may differ.

Palfridge (LTD) – Design specifications

Confidentiality: This document contains information, which is confidential. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without prior permission in writing. If you have received this document in error, please notify Palfridge Ltd immediately by e-mail (info@palfridge.com), facsimile (+268 2 5184126) or telephone (+268 2 5184196) and thereafter return and/or destroy the document. Palfridge Ltd accepts no liability (to the fullest extent permitted by law) for information in this document, which does not relate to its official business. No contracts or official orders shall be concluded by means of this document. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE