

FEATURES

Finish: Chromadek Steel External Sides & Internal Cabinet

Insulation: High Density Polyurethane Foam Insulation (CFC Free. Cyclopentane Blown)

Cooling System: Skin Evaporator

Baskets: No. of Baskets – 5
Basket Size – 445mm x 200mm x 220mm (Deep)
Basket Size – 445mm x 200mm x 125mm (Shallow)
Basket Capacity – 34.78 L
Basket Construction - Welded Steel Frame With Epoxy-polyester Powder Coating

Lid: Free Sliding Toughened Glass Lids (Curved & Slanted)

Lights: LED Strip



Optional Extras:

Voltage Protector | Stainless Steel Finish

Unit	Height	Width	Depth
FRZ Dimensions (mm)	630	1110	480
Cabinet Dimensions (mm)	850	1250	630
Packaging Dimensions (mm)	900	1270	640

Loading:

20 Ft	40 Ft	40 Ft	Tri	Inter	Super
		H/C	Axle	Link	Link
24	54	81	90	156	126

Literage	Total	FRZ	FRG
Gross Literage	246 L	246 L	N/A
Nett Literage	219 L	219 L	N/A

Model VI246-L

Type	Freezer
Model	VI246-L
Range	Commercial
Climate Class	Class 4
Star Rating	☆☆☆
H.S. Code	8418.30.00
FRZ Cap/24 ^{Hrs}	11.1Kg
Footprint Area	0.78 m ²
Cord Length	2.4 m
Weight	
Weight Boxed	

Q0824

* - Photo for illustrative purposes only. Actual unit may differ.

Palfridge (LTD) – Design specifications

Confidentiality: This document contains information, which is confidential. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without prior permission in writing. If you have received this document in error, please notify Palfridge Ltd immediately by e-mail (info@palfridge.com), facsimile (+268 2 5184126) or telephone (+268 2 5184196) and thereafter return and/or destroy the document. Palfridge Ltd accepts no liability (to the fullest extent permitted by law) for information in this document, which does not relate to its official business. No contracts or official orders shall be concluded by means of this document. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE